

Flat Roof Ventilation Skylight

Flat Roof Skylights provide a ventilation alternative perfect for allowing fresh air to flow into a working environment. Opened with a 280mm galvanised steel and brass manual spindle. An additional extension rod to open mechanism may be required. 300mm 24v DC Electric opener available on backorder (3-6 Weeks)



MATERIAL

- Triple Layer Polycarbonate (PC) Lid
- 150mm PVC Upstand
- Clear or Opal diffused layers

PERFORMANCE

- U-Value 1.8 W/m²K
- PVC Upstand U-value 1.1 W/m²K
- Sound reduction 22dB
- Manual Spindle opening up to 280mm (Electric available on backorder)

Layer Variant	Number of Layers	Light Transmittance	Solar Transmittance
Clear (Clear - Clear - Clear)	3 Layers	77%	64%
Opal (Opal - Clear - Clear)	3 Layers	44%	41%



Manual Spindle

Available Sizes

Nominal Size	Light Transmission Area m ²	Ventilation Area 280mm Manual	Ventilation Area 300mm Electric	Decibel Rating
600 x 600	0.18	0.18	0.18	22dB
600 x 900	0.30	0.30	0.30	22dB
900 x 900	0.52	0.40	0.43	22dB
1000 x 1000	0.67	0.46	0.49	22dB
1200 x 1200	1.04	0.57	0.61	22dB
1200 x 1800	1.65	-	0.79	22dB

CAD Drawings

